## Filics Unit - The double skid system for intralogistics pallet transportation

$\checkmark$	Minimal footprint	
--------------	-------------------	--

✓ Disappearing completely under the load carrier

- ✓ Maximal freedom of maneuverability
- ✓ Moving a pallet in any direction

✓ Drive through load carriers

Filics

✓ CE certified for human machine interaction

Unit Specification			CA Drive Concept		
<b>Dimensions</b> L x B x H	120 x 20 x 9 cm		Wheels per skid	4	
Weight per skid	< 50 kg		Drive System	omnidirectional	
Load Carriers focus, and others	Euro Pallet		Speed maximum	Unloaded: 2,0 m/s Loaded: 1,2 m/s	
1 ↓ Lift Concept			□ Battery Concept		
Lifting Modules	2		Туре	LiFePO4	
Lifting Height	9 cm		Runtime fully charged	4 hours	
Lifting Weight	600 kg		Charging Time empty battery	30 minutes	
(((o))) Sensors			Communication		
LIDAR	Localization, Navigation, Detection, Safety		Blue Spot	Driving Direction	
Camera	Detection, Safety		LED Strip	Status Notification	
Time of Light	Safety		Speakers	Acoustic Warning	

Balanstraße 73 81541 Munich, GER info@filics.eu